thereon an image-receiving layer comprising non-silicon-containing inorganic

oxide particles, said particles having their surfaces treated with a silane coupling

agent having a hydrophilic, organic moiety.

5

N

44

NJ

Ŋ

2. The pecording element of Claim 1 wherein said image-receiving

1. An ink jet recording element comprising a support having

10 layer contains said particles in an amount of from about 40 to about 95% by weight.

3. The recording element of Clair 1 wherein said inorganic oxide particles are pseudo-boehmite, alumina, zirconia, titania, yttria or ceria.

4. The recording element of Claim 1 wherein said inorganic oxide particles are treated with said silane coupling agent in an amount of from about 0.01 to about 0.5 mmbl/gram.

5. The recording element of Claim 1 wherein said silane coupling agent is N-(trimethoxysilylethyl)benzyl-N,N,N-trimethylammonium chloride; Ntrimethoxysilylpropyl-N,N,N-tributylammonium chloride; octadecyldimethyl(3rimethoxysilylpropyl)ammonium chloride; or N-(3-triethoxysilylpropyl)-4,5dihydroimidazole.

6. The recording element of Claim 1 wherein said image-receiving layer contains a polymeric binder

7. The recording element of Claim 6 wherein said polymeric binder is poly(vinyl alcohol).

15

20

- 8. The recording element of Claim 6 wherein said polymeric binder is present in an amount of from about 5 to about 30% by weight.
- 9. The recording element of Claim 1 wherein said imagereceiving layer is present at a thickness of from about 1 μm to about 60 μm.
- 10. The recording element of Claim 1 wherein said inorganic oxide particles have a particle size of from about 5 nm to about 1,000 nm.
- 11. The recording element of Claim 1 wherein a base layer is present in between said support and said image-receiving layer.
- 12. The recording element of Claim 11 wherein said base layer comprises inorganic particles and a polymeric binder.
- 13. The recording element of Claim 12 wherein said inorganic particles are calcium carbonate, calcined clay, aluminosilicates, zeolites or barium sulfate.
- 14. The recording element of Claim 12 wherein said polymeric binder is a styrene/acrylic latex, styrene/butadiene latex or poly(vinyl alcohol).

10

5

2

n n h